

Certificate of Conformity

Certificate Number: CN-PV-230110

On the basis of the tests undertaken, the sample<s> of the below product have been found to comply with the requirements of the referenced specification<s>/standard<s> at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture(s). The manufacturer(s) shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant: Inhenergy Co, Ltd

3/F & 4/F, Building 2, No. 35, Jinyuan 2nd Rd, Tangjiawan Town, Hi-Tech

Zone, Zhuhai, China.

Product: Hybrid Inverter

Ratings & Principle Characteristics:

See appendix of Certificate of Conformity

Model: HI-3K-SL, HI-3.6K-SL, HI-4K-SL, HI-5K-SL, HI-6K-SL

Brand Name<s>:

(INHENERGY

Product Complies with: RD647:2020

UNE 217002:2020

Certificate Issuing Office

Name & Address:

Intertek Testing Services Ltd. Shanghai

West Area, 2nd Floor, No. 707, Zhangyang Road

China (Shanghai) Pilot Free Trade Zone, Shanghai, P. R. China

Accredited by ACCREDIA in accordance with ISO/IEC 17065:2012

Test Report No.<s>: 230309063GZU-001

/ sustu

Additional information in Appendix.

Signature

Certification Manager: Grady Ye

Date: 17 March 2023



PRD Nº 306B

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-230110

MODEL	HI-3K-SL	HI-3.6K-SL	HI-4K-SL	HI-5K-SL	HI-6K-SL			
PV String Input data								
Max. Recommended PV power(kW)	7	7	9	9	9			
Max.DC voltage(V)	550							
Nominal voltage(V)	360							
MPPT working voltage range(V)	90~550							
Full load dc voltage range(V)	300~450							
Start Voltage/Minimum working voltage(V)	100/80							
Max. input Current of tracker A/tracker B (A)	15/15							
No. of independent MPP tracker MPPT tracker	2/1							
AC Output Data (Grid)								
Rated AC output power(KW)	3	3.6	4	5	6			
Max. AC apparent Power(kVA)	3.3	4	4.4	5.5	6.6			
Max. AC input power(KW)	6	7.2	8	10	12			
AC output voltage	230V, L+N+PE							
Rated AC output frequency	50 /60							
Rated AC output current (A)	13	15.6	18	22	26			
Max. AC input current (A)	28	32	38	48	58			
Power factor	±0.8							
AC Output Data (Back-up)	11	. //						
Max. AC output power(KVA)	3.3	4	4.4	5.5	6.6			
Rated AC output power(KW)	3	3.6	4	5	6			
Rated AC output voltage	230V, L+N+PE							
Rated AC output frequency	50 /60							

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-230110

Battery data								
Battery Type	Lithium /Lead-acid							
Nominal voltage(V)	48							
Battery voltage Range(V)	42~59							
Max.charging/discharging	80/80	80/80	100/100	100/100	100/100			
Capacity of battery	25-2000AH							
General Data	///			0				
Operating temperature	−25 °C~ +60 °C							
Environmental Protection	IP65							
Firmware version	HI 1.0							

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.