

230V Single Phase Grid-connected PV Inverter SI-7/10K-S2



- LED display, touch button design, direct data view
- Maximum efficiency 98.4%, dual MPPT, more power generation
- 14A string current, suitable for high current high efficiency module applications
- With 3-MPPT, support for parallel connection for greater adaptability
- 130% DC over configuration, 110% AC overload output; Wide DC voltage range
- IP65 protection, built-in SPD protection for safety and reliability
- Intelligent remote monitoring
- Support anti-backflow function



Technical Data	SI-7K-S2	SI-8K-S2	SI-9K-S2	SI-10K-S2
Input Data				
Max. DC input power	9100W	10400W	11700W	13000W
Max. DC input voltage	550V			
Operation voltage range	80V-540V			
Number of independent MPPT/ strings per MPPT	3/1+1+1			
MPPT max. current	14 A/14A/14A			
AC Output Data				
Rated output power	7kW	8kW	9kW	10 kW
Max. output power	7.7kW	8.8kW	9.9kW	10 kW
Rated output voltage	230V/180V-280V			
Rated output frequency	50Hz,60Hz/±5Hz			
Rated output current	30.5A	35A	39.2A	43.5A
Max. output current	34A	38.5A	43A	44A
Power factor	-0.8-+0.8(adjustable)			
THDi	<3%(Nominal Output)			
Grid system pattern	L+N+PE			
Efficiency				
Max. efficiency	98.4%			
Europe efficiency	97.5%			
Protection				
Input DC switch	Yes			
Input over current protection	Yes			
DC reverse polarity protection	Yes			
Output over voltage protection	Yes			
Output over current protection	Yes			
Anti islanding protection	Yes			
Insulation impedance protection	Yes			
RCD detection	Yes			
General Data				
Dimensions(W/L/H)in mm	358/400/ 180			
Weight	16kg			
Noise	<25dB		<45dB	
Operation temperature range	-25°C-+60°C			
Heat dissipation mode	Natural		Smart cooling	
IP Class	IP65			
Maximum altitude	4000m			
Self-Consumption night	<1w			
Topology	Transformerless			
Features				
LCD display	Yes			
Communication interface	WIFI/4G/GPRS/RS485(optional)			
Warranty	5 years (standard)			
Standards	IEC62109-1,IEC62109-2,NB/T32004,VDE-AR-N4105,EN50549,AS 4777			